Introduction to Network Security

Chapter 3

The Internet


Dr. Doug Jacobson - Introduction to Network Security - 2009 1

Topics


- The Internet
- Addressing
- Client Server
- Routing

The Internet

• User's View



Dr. Doug Jacobson - Introduction to Network Security - 2009 3




Dr. Doug Jacobson - Introduction to Network Security - 2009

Internet Addressing


- Different address types
- Hardware address spoofing
- IP address Spoofing
- IP address Space

Dr. Doug Jacobson - Introduction to Network Security - 2009

5



Dr. Doug Jacobson - Introduction to Network Security - 2009




Dr. Doug Jacobson - Introduction to Network Security - 2009

Address spoofing

- Who can generate the address?
- Spoofing is the ability to change the address
- Who can "see" (sniff) the traffic?

IP address Spoofing and Sniffing



IP Address Space

Dr. Doug Jacobson - Introduction to Network Security - 2009

- In Version 4 the IP address is 32 Bits
- Total IP address space is 4,294,967,296

IP addresses

 The IP address is written as a four-tuple where each tuple is in decimal and are separated by a "." (called a dot). When talking about an address you pronounce the word dot. So 129.186.5.102 is pronounced 129 dot 186 dot 5 dot 102

> Dr. Doug Jacobson - Introduction to Network Security - 2009

11

IP Addressing




Figure 3.5 Networks in the Internet Dr. Doug Jacobson - Introduction to Network Security - 2009

Machine names


- The format for the machine name is:
 - machine.domain Where:
 - machine is unique to the domain or subdomain.
 - and domain is a single domain or a series of subdomains.

Dr. Doug Jacobson - Introduction to Network Security - 2009 13

Domain Name Conversion

- Now lets look at how we can convert a machine name into an IP address.
- There are two ways that this conversion can take place.
 - The first is to use a table on each host which maintains the mapping between names and IP addresses. This method required very large tables and made it hard to update.
 - The second, and preferred, method is to use a nameserver. The nameserver is actually a set of nameservers each having authority over different domains and subdomains.


DNS Model




Client Server Model

Full name: server.dougj.net

IP address: Listening Port: 80




Client Server model



Client Server Model

Packets from client to server				
Source IP	Client's IP address			
Destination IP	Server's IP address			
Source Port	Ephemeral port			
Destination Port	Server's port number (often well known)			
Packets from server to client				
Source IP	Server's IP address			
Destination IP	Client's IP address			
Source Port	Server's port number (often well known)			
Destination Port	Ephemeral port			

Dr. Doug Jacobson - Introduction to Network Security - 2009



Multiple Connections

Stream	Source IP	Destination IP	Source Port	Destination Port
A	A	W1	Ephemeral A1	80
В	A	W1	Ephemeral A2	80
С	A	W1	Ephemeral A3	80
D	В	W1	Ephemeral B1	80
Е	В	W2	Ephemeral B2	80


Routing

- All hosts and gateways store routing tables
- Each row in the route table contains:
 - Destination address or address range
 - Next hop for that destination address range
 - The physical interface to use for that address range. (ie: which Ethernet card to use)

Example: **Destination Next Interface** 129.186.4.0 129.186.5.254 en0

Dr. Doug Jacobson - Introduction to Network Security - 2009 21

Routing



Dynamic vs Static

Static

- Tables built at system configuration time.
- Used in small networks or networks with only one way out

Dynamic


- Tables are modified based on network parameters
- Used in larger networks with multiple paths

Dr. Doug Jacobson - Introduction to Network Security - 2009

23

Destination Next Hop Network 1 Direct Default Router R1

Routing Example



Dr. Doug Jacobson - Introduction to Network Security - 2009